



BUTTWELD FITTINGS

ASTM A234 Grade W.P.B.

Caps

	METRIC NOM	Ø NOM	D	s	H	WEIGHT	
Standard weight 	15 mm	1/2"	21,3	2,80	25,4	0,032	
	20 mm	3/4"	26,7	2,95	31,7	0,059	
	25 mm	1"	33,5	3,40	38,1	0,101	
	32 mm	1.1/4"	42,2	3,55	38,1	0,141	
	40 mm	1.1/2"	48,3	3,70	38,1	0,172	
	50 mm	2"	60,4	3,90	38,1	0,231	
	65 mm	2.1/2"	73,1	5,20	38,1	0,371	
	80 mm	3"	88,9	5,45	50,8	0,641	
	100 mm	4"	114,3	5,95	63,5	1,16	
	125 mm	5"	141,2	6,45	76,2	1,91	
	150 mm	6"	168,4	7,10	88,9	14,4	
	200 mm	8"	219,2	8,25	101,6	5,13	
	250 mm	10"	273,-	9,25	127,-	9,08	
	300 mm	12"	323,8	9,50	152,4	10,4	
	350 mm	14"	355,6	9,55	165,1	16,-	
	400 mm	16"	406,4	9,55	177,8	20,1	
	450 mm	18"	457,2	9,55	203,2	25,9	
	500 mm	20"	508,-	9,55	228,6	32,5	
	600 mm	24"	609,6	9,55	266,7	46,3	
	Extra strong 	15 mm	1/2"	21,3	3,65	25,4	0,041
20 mm		3/4"	26,7	3,95	31,7	0,073	
25 mm		1"	33,5	4,55	38,1	0,131	
32 mm		1.1/4"	42,2	4,85	38,1	0,181	
40 mm		1.1/2"	48,3	5,10	38,1	0,221	
50 mm		2"	60,4	5,55	38,1	0,301	
65 mm		2.1/2"	73,1	7,10	38,1	0,460	
80 mm		3"	88,9	7,60	50,8	0,840	
90 mm		3.1/2"	101,6	8,15	63,5	1,28	
100 mm		4"	114,3	8,50	63,5	1,35	
125 mm		5"	141,2	9,50	76,2	2,61	
150 mm		6"	168,4	11,05	88,9	4,19	
200 mm		8"	219,2	12,70	101,6	7,40	
250 mm		10"	273,-	12,70	127,-	11,9	
300 mm		12"	323,8	12,70	152,4	17,3	
350 mm		14"	355,6	12,70	165,1	20,8	
400 mm		16"	406,4	12,70	177,8	26,1	
Schedule 30		200 mm	8"	219,2	7,00	101,6	4,60
		250 mm	10"	273,-	7,80	127,-	7,80
		300 mm	12"	323,8	8,40	152,4	12,-

